

METAL STRIP

Technical Data Sheet

Application: Metal Cleaner

Description

This high alkaline powdered dip tank cleaner designed for removing rust, carbonized soils and paint. It may be used in a variety of applications and industries to clean heavy equipment, remove rust and clean metal prior to painting or plating.

Directions

Add product to a partially filled container of cold water. Do not add to hot water. Gradually increase temperature after adding. The recommended concentration is 3 - 8% at a temperature of 80 - 90 °C. Contact time may vary from 30 minutes to 8 hours. When removed from dip tank rinse thoroughly with fresh water.

Personal Protective Equipment Required

- Impermeable gloves, clothing and boots
- NIOSH approved respirator
- Chemical goggles or safety glasses

General First Aid Information

• Inhalation

Remove victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel. Immediately transport victim to an emergency care facility.

• Ingestion

Rinse victim's mouth with water. **DO NOT INDUCE VOMITING.** Have victim drink 300 mL of water to dilute material in stomach. If milk is available, it may be given **AFTER** the water. Transport victim to an emergency facility.

• Skin Contact

In case of contact with skin, remove contaminated clothing and flush with water for at least 60 minutes. Do not interrupt flushing. Transport to an emergency facility.

• Eye Contact

In case of contact with eyes, continuously flush eyes with plenty of water or neutral saline solution for at least 60 minutes. Transport to emergency facility.

**For further safety information
please consult the MSDS**

Packaging Options

- 10 kg
- 20 kg
- 50 kg
- 150 kg

Physical Properties

State.....Solid
 Colour.....White
 Odour.....Odourless
 pH(1%).....12.5-13.5

TDG: Caustic Soda, Solid: Class 8,
UN1823, PG II



SCI-TECH

Engineered Chemicals

#340-53016 Hwy 60 Ph: 780-960-1200
 Acheson, AB T7X 5A7 Fx: 780-960-1201
www.scitechinc.ca